

Multicollar Slim

Universal Fire Collar



Fire resistance
≤ 120 minutes



Diameter
Ø 315 mm



Working life
30 years

ALL IN ONE

Universal Fire Collar

Multicollar *Slim* is a 30 mm-high universal fire collar that consists of a stainless steel band made of 174 segments and a high-quality inlay on a graphite basis. In order to achieve the desired pipe diameter, the links can easily be separated. In the event of fire, the Multicollar *Slim* starts foaming and creates a fire-resistant seal to adjacent rooms. In combination with the Multisealant A sealant, it is also possible to achieve a smoke-proof finish. This fire collar has been extensively tested in Europe in accordance with EN 1366-3. The Multicollar *Slim* fire collar is a single product for all applications. Thanks to the Multiclips and Multiscrews included in the box, one person can easily install it.

Multicollar *Slim* forms part of the Mulcol® Penetration Seal System.

Types of penetrations

- ✓ Standard plastic pipes
PVC-U, PVC-C, PP, PE, PE-HD, ABS, SAN+PVC
- ✓ Sound-proofing plastic pipes
REHAU Raupanio plus, Geberit Silent-20dB, Wavin SiTech+, Wavin AS, Blue Power, POLO-KAL 3S
- ✓ Aluminium composite pipes such as: PE-Xb, PE-Xc, PE-RT
Henco, Uponor, Wavin Tigris, Geberit Mepla, REHAU Rautitan
- ✓ Fibre composite pipes such as: PP-R, PP-B, PP-RCT
Aquatherm, Climatec, Aquatechnik
- ✓ Air-conditioning pipes such as: Wicu flex
- ✓ Copper and steel pipes
- ✓ Electric cables and cable bundles
- ✓ Cable pipes with and without electric cables
- ✓ Aluminium flue gas discharge pipes
- ✓ Concentric flue gas discharge pipes steel/PP

Tested configurations

- ✓ Pipes in combination with steel pipe support shells
- ✓ Angled pipes (¾ principle)
- ✓ Pipes with a zero distance from walls and floors, U-shaped collar
- ✓ Pipes under a 45° angle
- ✓ Pipes tested with tuck-in, electric welding and glue sleeves
- ✓ Pipes with 87°/90° and 2x 45° corner pieces
- ✓ Multiple pipe solutions
- ✓ Pipes with or without insulation

30 mm



Technical insulation


- ✓ Thermocompact® TF, PE-foam
- ✓ ABSound Sonocool Type PM
- ✓ Jaco Massa Reinforced Alu, Jaco Massa Alu and Jaco Massa Black Alu
- ✓ Merfisol Silver ALU
- ✓ AF/Armaflex and SH/Armaflex
- ✓ Kaiflex ST and Kaiflex KKplus s2
- ✓ Insul-Phen, Insul-Pirplus and Insul-Pir 33
- ✓ Kingspan Tarecpir M1, Kingspan Tarecpir CR, Kingspan Tarecpir B2, Kingspan Tarecpir HT
- ✓ Kingspan Tarecpir HD and Kingspan Kooltherm FM

Advantages

- ✓ Fire resistance ≤ 120 minutes
- ✓ Tested up to Ø 315 mm
- ✓ CE-certified
- ✓ Environmentally and user-friendly
- ✓ Easy to install
- ✓ One product for all applications
- ✓ One fixing medium for all structures
- ✓ Can be used anywhere thanks to its 30-mm height
- ✓ Also tested for non-standard applications
- ✓ User manual and all fasteners in one
- ✓ Damp, fungi and bacteria-resistant
- ✓ Halogen-free
- ✓ Working life of 30 years

Applications

- ✓ Rigid floors and walls
- ✓ Flexible walls
- ✓ Shaft walls
- ✓ Firestop Boards



Technical data

Colour stainless steel band + inlay	Stainless steel + Anthracite
Application temperature	+5 °C to +50 °C
Temperature resistance	-20 °C to +80 °C
Reaction to fire	Class E in accordance with EN 13501-1

Packaging

	Dimensions	Box	Outer box	Pallet	Article number
Roll (174 segments)	2610 x 30 x 12 mm	1 piece	8 pieces	384 pieces	206001174

Accessories (included)

- ✓ 20 pieces of Multiclips, 30 mm
- ✓ 20 pieces of Multiscrews 7,5 x 40 mm
- ✓ 1 piece of Multibit T30
- ✓ 6 pieces of Conformity Statement

Accessories (available separately)



Multiclip Set

20 pcs. Multiclip, 30 mm
20 pcs. Multiscrews 7,5 x 40 mm
Article number 802060001



Multiclip Set L

20 pcs. Multiclip L, 60 mm
20 pcs. Multiscrew 7,5 x 40 mm
Article number 802060002



Conformity Statement


Contents 6 pcs.
Article number 802060104







Multiscrew FB

20 pcs. Multiscrews FB, 40 mm for assembly on firestopping boards
Article number 802060005





Consumption table for plastic pipes

 Ø Pipe [mm]	 Segments	 Multiclip	 Multiclip Large	 Quantity/roll
16-40	15	2		11
50	17	2		10
56	18	2		9
63	19	2		9
75	22	2		7
80	23	2		7
90	25	2		6
100	27	3		6
110	29	3		6
125	32	3		5
140	36	3		4
160	40	4		4
200	48 (x2)	1	5	3 (1,8)
250	59 (x2)	2	5	2 (1,4)
315	72 (x2)	2	6	2 (1,2)



The remaining segments of the Multicollar Slim on the roll can simply be linked up using the enclosed Multiclips, thus enabling maximum use of the Multicollar Slim.

Please contact your Mulcol contact person for applications of plastic pipes and for the consumption overview of metal and aluminium composite pipes, aluminium flue gas discharge pipes and insulated pipes.

Technical documents available

- ✓ Product Data Sheet (PDS)
- ✓ Technical Data Sheet (TDS)
- ✓ Safety Data Sheet (SDS)
- ✓ Installation Manual
- ✓ EC certificate

Approvals

- ✓ Tested in accordance with EN 1366-3
- ✓ Classification in accordance with EN 13501-2
- ✓ Certified in accordance with EAD 350454-00-1104
- ✓ ETA report 17/0836
- ✓ Declaration of Performance (DoP)

The above documents are available from your Mulcol contact person or via www.mulcol.com



Information



Mulcol International composed the technical data on this sheet with great care and reserves the right to change product properties without prior notification. The user of this data remains responsible at all times for the correct application thereof. In the event of a lack of clarity or doubt, we recommend consulting Mulcol International to confirm that this data complies with the required application.